



NPT	L	H	W	∅
1/4	40	35	64	5
3/8	45	37	70	7
1/2	56	41	85	8.5
3/4	59	46	85	12.5
1	72	50	105	16
1 1/4	78	56.5	125	20
1 1/2	83	60	145	24
2	100	65.5	150	32

11	CAP	304	
10	WASHER	304	
9	BALL	304	
8	STEM	304	
7	NUT	304	
6	HANDLE	304	
5	GLUND NUT	304	
4	STUFFING	PTFE	
3	GASKET	PTFE	
2	SEALING-RING	PTFE	
1	BODY	CF8	
No.	NAME	MATERIAL	

PERFORMANCE AND SPECIFICATION	
NOMINAL PRESSURE	1.6MPa
TEST PRESSURE OF SHELL	2.4MPa
TEST PRESSURE OF SEALING	1.8MPa
TEST PRESSURE OF GAS SEALING	0.6MPa
WORKING TEMPERATURE	-20~150°C
APPLICABLE MEDIUMS	WATER-OIL-GAS

APPRD:	<p style="text-align: center;"><b>HANSETEC</b></p> <p style="text-align: center;">THREADS CONNECTION BALLVALVE</p> <p style="text-align: center;">1PQ11F16P-00</p>
CHKD:	
DRWN:	
DSGD:	
DATE:	